

DEWALT

FASTENS UP TO 443 LINEAR FEET OF DRYWALL TRACK**

INTERCHANGABLE CONTACT TRIPS

- Drywall and Stick-E™ contact trips for application versatility
- Magnetized - helps prevent ingestion of pin debris
- Removable; tool-free

DEPTH SETTING ADJUSTMENT SWITCH

- Normal embedment
- Deep embedment for difficult base materials

HIGH CAPACITY MAGAZINE

- Angled orientation allows access in tight areas
- Capacity of 36 fasteners
- Compatible with 1/2" to 1-1/2" fasteners

METERED FUEL CELL

1,000 fastenings per fuel cell

20V MAX* PLATFORM

This tool is a part of the DeWALT® 20V MAX* system featuring 300+ products.

TOOL WARRANTY

| | | |
|---|-------------------------------------|---|
| 3 YEAR LIMITED WARRANTY | 2 YEAR FREE SERVICE | 90 DAY MONEY BACK GUARANTEE |
|---|-------------------------------------|---|



TOOL CONNECT™ Chip-Ready
DCE042 (Sold Separately)



20V MAX* TRAK-IT® C6 GAS CONCRETE NAILER

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

** - in ambient temperature of 70 Degree Fahrenheit at sea level using 1 box of 1000 DeWALT Cordless Fasteners, DGN845080 fuel cell and DCB203 battery (Cordless Fasteners and fuel cell sold separately)

GUARANTEED TOUGH.®

DGN845

20V MAX* TRAK-IT® C6 GAS CONCRETE NAILER

GAS CONCRETE NAILERS

| CAT # | DESCRIPTION | MAGAZINE PIN LENGTH CAPACITY |
|----------|--|------------------------------|
| DGN845D1 | 20V MAX* TRAK-IT® C6 GAS CONCRETE NAILER (KIT) INCLUDES: DGN845 Tool, (1) DCB203 20V Max* Lithium Ion Battery (2ah), DGN8454 Trak-It® C6 1-1/2" Magazine, DGN8453 Standard/Drywall Kit Box Contact Trip, DCB1104 12V*/ 20V*/ FLEXVOLT® 4 Amp Charger, Kit Box | 1/2" - 1-1/2" |
| DGN845B | 20V MAX* TRAK-IT® C6 GAS CONCRETE NAILER (BARE TOOL) INCLUDES: DGN845 Tool, DGN8454 TRAK-IT® C6 1-1/2" Magazine, DGN8453 Standard/Drywall, Contact Trip, Kit Box | 1/2" - 1-1/2" |

COMPATIBLE ACCESSORIES

| CAT # | DESCRIPTION |
|-----------|---------------------------------|
| DGN8451 | Magnetic Stick-E™ Contact Trip |
| DGN8452 | Stick-E™ Contact Trip Piece |
| DGN8453 | Standard / Drywall Contact Trip |
| DGN845080 | Trak-It® C6 Fuel Cell |
| DGN8454 | Trak-It® C6 1-1/2" Magazine |

COMPATIBLE PINS

| CAT # | DESCRIPTION (LENGTH X DIA.) | RECOMMENDED APPLICATIONS | QTY | ICC ESR |
|--------------------------|-------------------------------|--|-------|----------|
| PINS FOR CONCRETE | | | | |
| DCN890075 | 3/4" .102" (Z) | Metal Track To Concrete | 1,000 | ESR-3275 |
| DCN890100 | 1" x .102" (Z) | Metal Track Or Fixture To Concrete Or Block | 1,000 | ESR-3275 |
| DCN890125 | 1-1/4" x .102" (Z) | Fixture Or Plywood To Concrete Or Block | 1,000 | ESR-3275 |
| DCN890150 | 1-1/2" x .102" (Z) | Plywood Or Sheathing To Concrete, Block Or Steel | 1,000 | ESR-3275 |
| DCN8912075 | 3/4" x .120" (T,Z) | Metal Track To Concrete | 1,000 | ESR-3275 |
| DCN891075 | 3/4" x .145" (Z) | Metal Track Or Fixture to Block or Light-Grade Concrete | 1,000 | ESR-3275 |
| DCN890110 | 1" x .145" (Z) | Metal Track, Plywood Rubber Membrane to Concrete, Steel Or Block | 1,000 | ESR-3275 |
| DCN890120 | 1-1/2" x .145" / .102" (S,Z) | Fixture to Concrete Or Block | 1,000 | ESR-3275 |
| DCN891125 | 1-1/4" x .145" / .120" (S,Z) | Fixture to Concrete Or Block | 1,000 | ESR-3275 |
| DCN890115 | 1-1/4" x .145" / .102" (S,Z) | Fixture to Concrete Or Block | 1,000 | ESR-3275 |
| PINS FOR STEEL | | | | |
| DCN8910500 | 1/2" x .120" (T,Z) | Metal track to steel | 1,000 | ESR-3275 |
| SPECIALTY PINS | | | | |
| DCN8941380 | 1-3/8" x .108" (K,Z) | Wood To Steel Stud | 1,000 | |
| DCN8910680 | .680" x .120" / .102" (S,YZ) | Metal Track to Steel, Hard Concrete, Or Post-Tension Concrete | 1,000 | ESR-3275 |
| DCN8917300 | .730" x .120" / .102" (S,YZ) | Metal Track to Steel, Hard Concrete, Or Post-Tension Concrete | 1,000 | ESR-3275 |
| DCN8907804 | .780" x .102" / .088" (K,S,Z) | Fixture to Steel, Hard Concrete, Or Post-Tension Concrete | 1,000 | |

K: Knurled S: Step T: Tapered YZ: Yellow Zinc Z: Zinc

Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

Copyright ©2025 DEWALT. The following are examples of trademarks for one or more DEWALT power tools and accessories: the yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.



STICK-E™ ACCESSORIES

| CAT # | DESCRIPTION | QTY | MSTR |
|------------|-------------------------------------|-----|------|
| DFD405101 | LATHING WASHER 1" | 100 | 1000 |
| DFD405100 | LATHING WASHER 1" (NO STICK-E) | 100 | 1000 |
| DFD405716 | INSULATION WASHER 1-7/16" | 100 | 1000 |
| DFD405901 | DENZ GLASS WASHER | 250 | 2500 |
| DFD405338 | BX CLIP 3/8" | 100 | 1000 |
| DFD405412 | CONDUIT CLIPS 1/2" | 50 | 200 |
| DFD405434 | CONDUIT CLIPS 3/4" | 50 | 200 |
| DFD405410 | CONDUIT CLIPS 1" | 50 | 100 |
| DFD405312R | MINI CONDUIT CLAMP 1/2" | 100 | 1000 |
| DFD405334R | MINI CONDUIT CLAMP 3/4" | 100 | 1000 |
| DFD405310R | MINI CONDUIT CLAMP 1" | 100 | 1000 |
| DFD405902 | CABLE TIE DONUT 1-1/4" | 100 | 1000 |
| DFD405550 | RIGHT ANGLE CLIP 90° | 100 | 1000 |
| DFD405530 | ANGLE CLIP 60° | 100 | 1000 |
| DFD405214 | ROD HANGER 1/4"-20 | 100 | 1000 |
| DFD405238 | ROD HANGER 3/8"-16 | 100 | 1000 |
| DFD405215 | POST NUT HANGER 1/4"-20 | 100 | 1000 |
| DFD405239 | POST NUT HANGER 3/8"-16 | 100 | 1000 |
| DFD405112 | STRAP METAL WASHER 1/2" | 100 | 1000 |
| DFD405300 | REBAR/DOWEL BASKET CLIP | 100 | 1000 |
| DFD405610 | SQUARE WASHER 1" | 100 | 1000 |
| DFD405102 | STAINLESS STEEL SEALING WASHER 3/4" | 100 | 1000 |

DGN845SS

GUARANTEED TOUGH.®

1-800-4-DEWALT

www.DEWALT.com