

**GAS DIRECT FASTENING SELECTION GUIDE**

Pins / Fasteners Description	Dimensions		Base Material						Stick-E Accessories	Approvals & Listings
	Shank Diameter	Shank Length	Concrete	Lightweight Concrete	Concrete over Steel Deck	Concrete Masonry (CMU)	Steel	Light Gauge Steel		
<b>Trak-It C5</b> Straight Shank Pins	0.102"	3/4" to 1-1/2"	●	●	●	●			●	ESR-3275
Tapered Shank Pins	0.120"	1/2"						●		ESR-3275
Tapered Shank Pins	0.120"	3/4"	●	●	●	●				ESR-3275
Straight Shank Pins	0.145"	3/4" to 1"	●	●	●	●				ESR-3275
Step Shank Pins	0.145"/0.102"	1-1/4" to 1-1/2"	●	●	●	●				ESR-3275
Step Shank Pins	0.145"/0.120" (K)	1" to 1-1/4"	●	○		●	●			ESR-3275
Step Shank Pins	0.120/0.102" (K)	0.680" to 0.730"	●	○			●			ESR-3275
Step Shank Pins	0.102/0.088" (K)	0.780"	●	○	○	●	○		●	
Spiral Shank Pin	0.108" (K)	1-3/8"						●	Denz Glass Washer	

● Suitable ○ May be Suitable  
(K) = Knurled