	SAFETY DATA SHEET	Page : 1 / 14
		Version: 4.0
		Issue date: 04/01/2020
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Supersedes: 07/18/2017

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name/designation : HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Building and construction work

1.3. Details of the supplier of the safety data sheet

DeWALT Industrial Tool Co.
701 East Joppa Road
Toowson, MD 21286 USAp
T +1 800-524-3244 - F +1 877-871-1965

1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-424-9300 (within Continental USA)
CHEMTREC +1 703 527-3887 (outside USA)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3	H226
Acute toxicity (oral) Category 4	H302
Skin corrosion/irritation Category 2	H315
Serious eye damage/eye irritation Category 2A	H319
Skin sensitization, Category 1	H317
Reproductive toxicity Category 1B	H360
Specific target organ toxicity (repeated exposure) Category 1	H372

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :

		
GHS02	GHS07	GHS08


Signal word (GHS US) : Danger

Hazard statements (GHS US) :

- H226 - Flammable liquid and vapour
- H302 - Harmful if swallowed
- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H319 - Causes serious eye irritation
- H360 - May damage fertility or the unborn child
- H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

- P102 - Keep out of reach of children.
- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

	SAFETY DATA SHEET	Page : 2 / 14
		Version: 4.0
		Issue date: 04/01/2020
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Supersedes: 07/18/2017

sources. No smoking.
P233 - Keep container tightly closed.
P260 - Do not breathe dust, mist.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P301+P312 - If swallowed: Call a doctor, a POISON CENTER if you feel unwell.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P330 - Rinse mouth.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to an approved waste disposal plant.

2.3. Other hazards

Other hazards : PBT/vPvB data : This information is not available.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Substance name	Product identifier	%	GHS US classification
Styrene	(CAS-No.) 100-42-5	10 - 25	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 2, H361 STOT SE 3, H335 STOT RE 1, H372 Asp. Tox. 1, H304
dicyclohexyl phthalate	(CAS-No.) 84-61-7	1 - 2.5	Skin Sens. 1, H317 Repr. 1B, H360
Dibenzoyl peroxide	(CAS-No.) 94-36-0	1 - <2.5	Org. Perox. B, H241 Eye Irrit. 2A, H319 Skin Sens. 1, H317
2-Propanol, 1,1'-[(4-methylphenyl)imino]bis-	(CAS-No.) 38668-48-3	0 - 1.25	Acute Tox. 2 (Oral), H300


Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : First aider: Pay attention to self-protection!. See also section 8. Never give anything by mouth to an unconscious person. Show this safety data sheet to the doctor in attendance. Treat symptomatically.

Inhalation : Provide fresh air. Put victim at rest, cover with a blanket and keep warm. In case of doubt or persistent symptoms, consult always a physician.

	SAFETY DATA SHEET	Page : 3 / 14
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Version: 4.0
		Issue date: 04/01/2020
		Supersedes: 07/18/2017

Skin contact : Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water . Call a physician if irritation develops or persists.

Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of doubt or persistent symptoms, consult always a physician.

Ingestion : Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation : No adverse effects are expected. May be irritating.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Harmful if swallowed.

Chronic symptoms : Causes damage to organs through prolonged or repeated exposure. May damage the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray, Alcohol resistant foam, Carbon dioxide, Dry extinguishing powder.

Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Flammable liquid and vapour. Hazardous decomposition products COx. Do not allow run-off from fire-fighting to enter drains or water courses.

Reactivity : Flammable liquid and vapor. Reference to other sections: 10.5.

5.3. Advice for firefighters

Firefighting instructions : Special protective equipment for firefighters. Use water spray or fog for cooling exposed containers. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel


For non-emergency personnel : Evacuate personnel to a safe area. Use personal protective equipment as required. Reference to other sections: 8. Provide adequate ventilation. Avoid contact with skin, eyes and clothing. Do not breathe vapors/dust. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is adequately grounded. Take precautionary measures against static discharges.

6.1.2. For emergency responders

For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see item 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

	SAFETY DATA SHEET	Page : 4 / 14
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Version: 4.0
Issue date: 04/01/2020		
Supersedes: 07/18/2017		

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Take up mechanically and collect in suitable container for disposal. Collect in closed and suitable containers for disposal. Dam up. Dispose of contaminated materials in accordance with current regulations.

6.4. Reference to other sections

Concerning personal protective equipment to use, see item 8. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only in well ventilated areas. Use personal protective equipment as required. Concerning personal protective equipment to use, see item 8 . Avoid contact with skin, eyes and clothing. Do not breathe vapor/aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle and open container with care. After use replace the closing cap immediately. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Do not allow to enter into surface water or drains. Take any precaution to avoid mixing with combustibles. See also section 10 .

Hygiene measures : Keep good industrial hygiene. Wash hands and face before breaks and immediately after handling of the product. Take off contaminated clothing.

7.2. Conditions for safe storage, including any incompatibilities


Technical measures : Keep container tightly closed in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from food, drink and animal feedingstuffs. Keep at temperatures below 25 °C. Keep away from heat. Protect from sunlight. Do not store near or with any of the incompatible materials listed in section 10.

Incompatible substances or mixtures : Strong acids. Strong bases. Strong oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Styrene (100-42-5)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	40 ppm
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm
IDLH	US IDLH (ppm)	700 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	215 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	425 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	100 ppm
2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)		
Not applicable		
Dibenzoyl peroxide (94-36-0)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³

	SAFETY DATA SHEET	Page : 5 / 14
		Version: 4.0
		Issue date: 04/01/2020
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Supersedes: 07/18/2017

Dibenzoyl peroxide (94-36-0)		
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
IDLH	US IDLH (mg/m ³)	1500 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³

dicyclohexyl phthalate (84-61-7)	
Not applicable	

Monitoring methods	
Monitoring methods	Concentration measurement in air, Personal air monitoring

Additional information : Concentration measurement in air
Personal monitoring

8.2. Exposure controls

- Engineering measure(s) : Use only in area provided with appropriate exhaust ventilation. Take precautionary measures against static discharge. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Organizational measures to prevent /limit releases, dispersion and exposure. See also section 7.
- Personal protective equipment : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
- Hand protection : Wear chemically resistant gloves. Impervious gloves. The selection of specific gloves for a specific application and time of use in a working area, should also take into account other factors on the working space, such as (but not limited to): other chemicals that are possibly used, physical requirements (protection against cutting/drilling, skill, thermal protection), and the instructions/specification of the supplier of gloves. Breakthrough time : >8 hours. VITON gloves. Thickness of the glove material: 0,7 mm. Nitrile rubber. Breakthrough time : <1 hours.
- Eye protection : Chemical goggles or safety glasses (EN 166).
- Body protection : Wear suitable protective clothing.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Wear a full face respirator, NIOSH certified. Half-face mask (DIN EN 140). Filter type: A (EN 141).
- Thermal hazard protection : Not required for normal conditions of use.
- Environmental exposure controls : Do not allow to enter into surface water or drains. Comply with applicable environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : capsules.
: No data available
: No data available
- Odor threshold : No data available
- pH : No data available
- Melting / freezing point : No data available
- Freezing point : No data available

	SAFETY DATA SHEET	Page : 6 / 14
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Version: 4.0
		Issue date: 04/01/2020
		Supersedes: 07/18/2017

Initial boiling point and boiling range	: No data available
Flash point	: < 131 °F Resin
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidizing properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with explosive properties.
Vapor pressure	: No data available
Relative density	: No data available
Vapor density	: No data available
Solubility	: No additional information available. Water: insoluble
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: 400 - 500 mPa·s Resin
Kinematic viscosity	: No data available
Dynamic viscosity	: 400 - 500 mPa·s (Resin)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor. Reference to other sections: 10.5.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

heat : Polymerization can occur.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. UV-radiation/sunlight. See also section 7. Handling and storage.

10.5. Incompatible materials

Strong oxidizing agents. Strong bases. Strong acids. See also section 7. Handling and storage.


10.6. Hazardous decomposition products

Burning produces noxious and toxic fumes. (COx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

	SAFETY DATA SHEET	Page : 7 / 14
		Version: 4.0
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Issue date: 04/01/2020
		Supersedes: 07/18/2017

HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	
ATE US (oral)	391,466 mg/kg body weight

Styrene (100-42-5)	
LD50 oral rat	1000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	11,8 mg/l
ATE US (oral)	1000 mg/kg body weight
ATE US (vapors)	11,8 mg/l/4h
ATE US (dust, mist)	1,5 mg/l/4h

2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)	
ATE US (oral)	5 mg/kg body weight

Dibenzoyl peroxide (94-36-0)	
LD50 oral rat	7710 mg/kg
ATE US (oral)	7710 mg/kg body weight

dicyclohexyl phthalate (84-61-7)	
LD50 oral rat	30 ml/kg
ATE US (oral)	30000 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.
pH: No data available

Serious eye damage/irritation : Causes serious eye irritation.
pH: No data available

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Styrene (100-42-5)	
IARC group	2A - Probably carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes

Dibenzoyl peroxide (94-36-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : May damage fertility or the unborn child.

STOT-single exposure : Not classified

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.


Aspiration hazard : Not classified

Inhalation : No adverse effects are expected. May be irritating.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Harmful if swallowed.

	SAFETY DATA SHEET	Page : 8 / 14
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Version: 4.0
		Issue date: 04/01/2020
		Supersedes: 07/18/2017

Chronic symptoms : Causes damage to organs through prolonged or repeated exposure. May damage the unborn child.

Other information : Symptoms related to the physical, chemical and toxicological characteristics.
Reference to other sections: 4.2.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects .

Styrene (100-42-5)	
LC50 fish 1	3,24 - 4,99 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3,3 - 7,4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	1,4 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	19,03 - 33,53 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 other aquatic organisms 2	500 mg/l Bacteria
EC50 other aquatic organisms 2	0,72 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
NOEC (acute)	44 mg/kg (Exposure time: 14 Days - Species: Eisenia foetida [soil dry weight])
NOEC (additional information)	NOEC, Daphnia : 1,01 mg/l (21d)
2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)	
LC50 fish 1	17 mg/l (Exposure time: 96 h - Species: Danio rerio [static])
Dibenzoyl peroxide (94-36-0)	
LC50 fish 1	0,0602 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])

12.2. Persistence and degradability


HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	
Persistence and degradability	No data available.
Styrene (100-42-5)	
Biodegradation	Readily biodegradable

12.3. Bioaccumulative potential

HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	
Partition coefficient n-octanol/water	No data available
Bioaccumulative potential	No additional information available.
Styrene (100-42-5)	
BCF fish 1	13,5
Partition coefficient n-octanol/water	2,95
Bioaccumulative potential	Does not bioaccumulate.

12.4. Mobility in soil

HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	
Mobility in soil	No data available
Ecology - soil	No data available.
Styrene (100-42-5)	
Log Koc	352 (20°C)

	SAFETY DATA SHEET	Page : 9 / 14
		Version: 4.0
		Issue date: 04/01/2020
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Supersedes: 07/18/2017

12.5. Other adverse effects

Other information : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Handle with care. Safe handling: see section 7. Handling and storage. Do not allow to enter into surface water or drains. Dispose of contaminated materials in accordance with current regulations. Refer to manufacturer/supplier for information on recovery/recycling. Collect and dispose of waste product at an authorized disposal facility.

Additional information : In accordance with local and national regulations.

Further ecological information : Should not be released into the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1866 Resin solution, 3, III

UN-No.(DOT) : UN1866

Proper Shipping Name (DOT) : Resin solution

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

Special provisions : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

	SAFETY DATA SHEET	Page : 10 / 14
		Version: 4.0
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Issue date: 04/01/2020
		Supersedes: 07/18/2017

DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 127
Other information	: No supplementary information available.
Special precautions for user	: No data available.
IBC code	: No data available.

Transportation of Dangerous Goods

Transport document description	: UN1866 RESIN SOLUTION, 3, III
UN-No. (TDG)	: UN1866
Proper Shipping Name (Transportation of Dangerous Goods)	: RESIN SOLUTION
TDG Primary Hazard Classes	: 3 - Class 3 - Flammable Liquids
Packing group	: III - Minor Danger
Explosive Limit and Limited Quantity Index	: 5 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L

Transport by sea

UN-No. (IMDG)	: 1866
Proper Shipping Name (IMDG)	: RESIN SOLUTION
Class or Division	: 3 - flammable liquids
Packing group (IMDG)	: III - substances presenting low danger


Air transport

UN-No. (IATA)	: 1866
Proper Shipping Name (IATA)	: Resin solution
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Styrene (100-42-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
SARA Section 313 - Emission Reporting	0,1 %
2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

	SAFETY DATA SHEET	Page : 11 / 14
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Version: 4.0
		Issue date: 04/01/2020
		Supersedes: 07/18/2017

Dibenzoyl peroxide (94-36-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 %
dicyclohexyl phthalate (84-61-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA


Styrene (100-42-5)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)	
Listed on the Canadian DSL (Domestic Substances List)	
Dibenzoyl peroxide (94-36-0)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class C - Oxidizing Material Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class F - Dangerously Reactive Material
dicyclohexyl phthalate (84-61-7)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

Styrene (100-42-5)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
Dibenzoyl peroxide (94-36-0)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
dicyclohexyl phthalate (84-61-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

National regulations

Styrene (100-42-5)	
Listed on the AICS (Australian Inventory of Chemical Substances)	
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)	
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory	
Listed on the Japanese ISHL (Industrial Safety and Health Law)	
Listed on the Korean ECL (Existing Chemicals List)	
Listed on NZIoC (New Zealand Inventory of Chemicals)	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)	
Japanese Pollutant Release and Transfer Register Law (PRTR Law)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
Listed on INSQ (Mexican National Inventory of Chemical Substances)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
Listed on the TCSI (Taiwan Chemical Substance Inventory)	

	SAFETY DATA SHEET	Page : 12 / 14
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Version: 4.0
		Issue date: 04/01/2020
		Supersedes: 07/18/2017

2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Japanese ISHL (Industrial Safety and Health Law)
 Listed on the Korean ECL (Existing Chemicals List)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on the TCSI (Taiwan Chemical Substance Inventory)

Dibenzoyl peroxide (94-36-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Japanese ISHL (Industrial Safety and Health Law)
 Listed on the Korean ECL (Existing Chemicals List)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on the Canadian IDL (Ingredient Disclosure List)
 Listed on INSQ (Mexican National Inventory of Chemical Substances)
 Listed on the TCSI (Taiwan Chemical Substance Inventory)

dicyclohexyl phthalate (84-61-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Japanese ISHL (Industrial Safety and Health Law)
 Listed on the Korean ECL (Existing Chemicals List)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Japanese Pollutant Release and Transfer Register Law (PRTR Law)
 Listed on INSQ (Mexican National Inventory of Chemical Substances)
 Listed on the TCSI (Taiwan Chemical Substance Inventory)


15.3. US State regulations

Styrene (100-42-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	27 µg/day

SECTION 16: Other information

Sources of key data used to compile the datasheet : LOLI. Supplier information.

	SAFETY DATA SHEET	Page : 13 / 14
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Version: 4.0
		Supersedes: 07/18/2017

Abbreviations and acronyms

: ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods Code
LEL = Lower Explosive Limit/Lower Explosion Limit
UEL = Upper Explosion Limit/Upper Explosive Limit
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals.
EC50 = Median Effective Concentration. LC50 = Median lethal concentration. LD50 = Median lethal dose. Not applicable. TLV = Threshold limits. TWA = time weighted average. STEL = Short term exposure limit. persistent, bioaccumulating and toxic (PBT). vPvB = very persistent and very bioaccumulating. WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act).

Training advice

: Training staff on good practice. Manipulations are to be done only by qualified and authorized persons.

Other information

: Assessment/classification GHS. Calculation method. Physicochemical hazard assessment: Information given is based on tests on the mixture itself.

Full text of H-phrases:

H226	Flammable liquid and vapour
H241	Heating may cause a fire or explosion
H300	Fatal if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H360	May damage fertility or the unborn child
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

NFPA health hazard


: 1 - Materials that, under emergency conditions, can cause significant irritation.


NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



	SAFETY DATA SHEET	Page : 14 / 14
		Version: 4.0
	Hammer Capsule HC 3/8", HC 1/2", HC 5/8", HC 3/4", HC 7/8", HC 1"	Issue date: 04/01/2020
		Supersedes: 07/18/2017

Hazard Rating

- Health : 1 Slight Hazard - Irritation or minor reversible injury possible
- Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)
- Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
- Personal protection : B
B - Safety glasses, Gloves

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.