

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.10.2023

Version number 1

Revision: 18.10.2023

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Trade name: TRIGGERFOAM WINDOW & DOOR

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture - One-component polyurethane foam - gun grade

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

DEWALT Industrial Tools  
701 East Joppa Road  
Towson, MD 21286  
USA

#### Further information obtainable from:

Phone: +1 800-524-3244

Fax: +1 877-871-1965

### 1.4 Emergency telephone number: - In case of emergency, consult physician

CHEMTREC: 800-424-9300 (within continental USA)

CHEMTREC: +1 703 527-3887 (outside USA)

-

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
Lact.	H362	May cause harm to breast-fed children.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 4	H413	May cause long lasting harmful effects to aquatic life.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

EU

**Trade name: TRIGGERFOAM WINDOW & DOOR**

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labelling:**diphenylmethanediisocyanate, isomers and homologues  
alkanes, C14-17, chloro· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H332 Harmful if inhaled.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H362 May cause harm to breast-fed children.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H413 May cause long lasting harmful effects to aquatic life.

· **Precautionary statements**

P102 Keep out of reach of children.  
P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection.  
P284 In case of inadequate ventilation wear respiratory protection (a protective mask with an appropriate gas filter - i.e. type A1 according to standard EN 14387).  
P302+P352 IF ON SKIN: Wash with plenty of water/soap.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of container in accordance with local/regional/national/international regulation.

· **Additional information:**

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from 24 August 2023 adequate training is required before industrial or professional use.  
EUH204 Contains isocyanates. May produce an allergic reaction.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment** Not applicable.

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.10.2023

Version number 1

Revision: 18.10.2023

**Trade name: TRIGGERFOAM WINDOW & DOOR**

(Contd. of page 2)

· **PBT:**

CAS: 85535-85-9 alkanes, C14-17, chloro

· **vPvB:**

CAS: 85535-85-9 alkanes, C14-17, chloro

### SECTION 3: Composition/information on ingredients

· **3.1 Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	45-55%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-15%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-01-8	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-10%
CAS: 13674-84-5 EINECS: 237-158-7	tris(2-chlorisopropyl)-phosphate ⚠ Acute Tox. 4, H302	1-10%
CAS: 85535-85-9 EINECS: 287-477-0 Index number: 602-095-00-X	alkanes, C14-17, chloro ⚠ Acute Tox. 2, H330; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362, EUH066 PBT; vPvB	1-10%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-5%

· **SVHC**

CAS: 85535-85-9 alkanes, C14-17, chloro

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.10.2023

Version number 1

Revision: 18.10.2023

**Trade name: TRIGGERFOAM WINDOW & DOOR**

(Contd. of page 3)

- **After skin contact:**  
If skin irritation continues, consult a doctor.  
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Foam  
CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
In case of fire, the following can be released:  
Nitrogen oxides (NO<sub>x</sub>)  
Carbon monoxide (CO)  
Hydrogen cyanide (HCN)
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
- **Additional information**  
Cool endangered receptacles with water spray.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Keep away from ignition sources.  
Ensure adequate ventilation  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow to enter sewers/ surface or ground water.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow product to reach sewage system or any water course.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to section 13.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Do not flush with water or aqueous cleansing agents  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 5)

EU

**Trade name: TRIGGERFOAM WINDOW & DOOR**

See Section 13 for disposal information.

(Contd. of page 4)

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Ensure that suitable extractors are available on processing machines  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurised containers.

**Information about storage in one common storage facility:**

Do not store together with acids.  
Do not store together with alkalis (caustic solutions).  
Store away from oxidising agents.

**Further information about storage conditions:**

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.  
Protect from humidity and water.  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 115-10-6 dimethyl ether**IOELV Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm**Additional information:** The lists valid during the making were used as basis.**8.2 Exposure controls****Appropriate engineering controls** No further data; see section 7.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

**Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)

**Trade name: TRIGGERFOAM WINDOW & DOOR**

(Contd. of page 5)

**· Hand protection**

Protective gloves

Protective gloves according to EN 374.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye/face protection**

Tightly sealed goggles

Wear airtight protective goggles EN 166

**· Body protection: Protective work clothing EN 13688****SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Physical state**

Aerosol

**· Colour:**

According to product specification

**· Odour:**

Characteristic

**· Odour threshold:**

Not determined.

**· Melting point/freezing point:**

Undetermined.

**· Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

**· Flammability**

Contact with water liberates extremely flammable gases.

**· Lower and upper explosion limit****· Lower:**

3.0 Vol % (CAS: 115-10-6 dimethyl ether)

**· Upper:**

18.6 Vol % (CAS: 115-10-6 dimethyl ether)

**· Flash point:**

Not applicable, as aerosol.

**· Auto-ignition temperature:**

199 °C

**· Decomposition temperature:**

Not determined.

**· pH**

Not determined.

**· Viscosity:****· Kinematic viscosity**

Not determined.

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.10.2023

Version number 1

Revision: 18.10.2023

**Trade name: TRIGGERFOAM WINDOW & DOOR**

(Contd. of page 6)

· <b>Dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure:</b>	Not determined.
· <b>Density and/or relative density</b>	
· <b>Density:</b>	Not determined.
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
<b>9.2 Other information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Aerosol
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Not determined.
· <b>Solvent content:</b>	
· <b>VOC (EC)</b>	185.6 g/l 18.30 %
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not applicable.
<b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.

(Contd. on page 8)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.10.2023

Version number 1

Revision: 18.10.2023

**Trade name: TRIGGERFOAM WINDOW & DOOR**

(Contd. of page 7)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Contact with water releases flammable gases.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Hydrogen cyanide (prussic acid)  
Carbon monoxide  
Nitrogen oxides (NOx)

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**  
Harmful if inhaled.
- **LD/LC50 values relevant for classification:**

<b>CAS: 115-10-6 dimethyl ether</b>		
Inhalative	LC50/4 h	308 mg/l (rat)
<b>CAS: 13674-84-5 tris(2-chlorisopropyl)-phosphate</b>		
Oral	LD50	3,600 mg/kg (rat)
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation**  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**  
Suspected of causing cancer.
- **Reproductive toxicity**  
May cause harm to breast-fed children.
- **STOT-single exposure**  
May cause respiratory irritation.
- **STOT-repeated exposure**  
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.

(Contd. on page 9)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.10.2023

Version number 1

Revision: 18.10.2023

**Trade name: TRIGGERFOAM WINDOW & DOOR**

(Contd. of page 8)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment** Not applicable.

· **PBT:**

CAS: 85535-85-9 alkanes, C14-17, chloro

· **vPvB:**

CAS: 85535-85-9 alkanes, C14-17, chloro

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**· **Remark:** Toxic for fish· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

**SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 05 01\* waste isocyanates

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

15 01 10\* packaging containing residues of or contaminated by hazardous substances

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information**· **14.1 UN number or ID number**· **ADR, IMDG, IATA** 1950· **14.2 UN proper shipping name**· **ADR** 1950 AEROSOLS· **IMDG, IATA** AEROSOLS· **14.3 Transport hazard class(es)**· **ADR**· **Class** 2 5F Gases.· **Label** 2.1· **IMDG, IATA**· **Class** 2.1 Gases.

(Contd. on page 10)

**Trade name: TRIGGERFOAM WINDOW & DOOR**

(Contd. of page 9)

· Label	2.1
· <b>14.4 Packing group</b>	
· ADR, IMDG, IATA	Void
· <b>14.5 Environmental hazards:</b>	
· Marine pollutant:	No
· <b>14.6 Special precautions for user</b>	Warning: Gases.
· EMS Number:	F-D,S-U
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

COMMISSION REGULATION (EU) 2020/878  
amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P3a FLAMMABLE AEROSOLS**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

(Contd. on page 11)

**Trade name: TRIGGERFOAM WINDOW & DOOR**

(Contd. of page 10)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H362 May cause harm to breast-fed children.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH204 Contains isocyanates. May produce an allergic reaction.

### · Abbreviations and acronyms:

- Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Acute Tox. 2: Acute toxicity – Category 2
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Resp. Sens. 1: Respiratory sensitisation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Carc. 2: Carcinogenicity – Category 2
- Lact.: Reproductive toxicity – effects on or via lactation
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
- Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4