

## 1 Identification

- **Product identifier**
- **Trade name:** TRIGGERFOAM PRO WINDOW AND DOOR
- **Application of the substance / the mixture** One Component Polyurethane B2 Foam Sealant
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
DEWALT Industrial Tools  
701 East Joppa Road  
Towson, MD 21286  
USA
- **Information department:**  
Telephone: 800-524-3244  
Telefax: 877-871-1965
- **Emergency telephone number:**  
CHEMTREC: 800-424-9300 (within continental USA)  
CHEMTREC: +1 703 527-3887 (outside USA)

## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Flam. Aerosol 1 H222 Extremely flammable aerosol.  
H229 Pressurized container: May burst if heated.  
Aquatic Chr. 4 H413 May cause long lasting harmful effects to aquatic life.  
Acute Tox. 4 H332 Harmful if inhaled.  
Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2A H319 Causes serious eye irritation.  
Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
Carc. 2 H351 Suspected of causing cancer.  
Lact. H362 May cause harm to breast-fed children.  
STOT SE 3 H335 May cause respiratory irritation.  
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

diphenylmethanediisocyanate, isomers and homologues

- **Hazard statements**

Extremely flammable aerosol.

Pressurized container: May burst if heated.

May cause long lasting harmful effects to aquatic life.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Harmful if inhaled.

(Contd. on page 2)

**Trade name: TRIGGERFOAM PRO WINDOW AND DOOR**

(Contd. of page 1)

- May cause an allergic skin reaction.
- Suspected of causing cancer.
- May cause harm to breast-fed children.
- May cause respiratory irritation.
- May cause damage to organs through prolonged or repeated exposure.

• **Precautionary statements**

- Obtain special instructions before use.
- Keep out of reach of children.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Do not spray on an open flame or other ignition source.
- Do not pierce or burn, even after use.
- Do not breathe vapours/spray.
- Wear protective gloves/protective clothing/eye protection.
- In case of inadequate ventilation wear respiratory protection (a protective mask with an appropriate gas filter - i.e. type A1 according to standard EN 14387).
- If on skin: Wash with plenty of water/soap.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF exposed or concerned: Get medical advice/attention.
- Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- Dispose of container to in accordance with local/regional/national/international regulation.

- **Additional information:** Contains isocyanates. May produce an allergic reaction.

• **NFPA ratings (scale 0 - 4)**



Health = 1  
Fire = 0  
Reactivity = 3

• **HMIS-ratings (scale 0 - 4)**



Health = 1  
Fire = 0  
Reactivity = 3

**3 Composition/information on ingredients**

• **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

• **Dangerous components:**

|                 |   |        |
|-----------------|---|--------|
| CAS: 9016-87-9  | diphenylmethanediisocyanate, isomers and homologues | 40-50% |
| CAS: 115-10-6   | dimethyl ether                                      | 1-10%  |
| CAS: 13674-84-5 | tris(2-chlorisopropyl)-phosphate                    | 1-10%  |
| CAS: 85535-85-9 | alkanes, C14-17, chloro                             | 1-10%  |
| CAS: 75-28-5    | isobutane   | 1-10%  |
| CAS: 74-98-6    | propane   | <5%    |

**4 First-aid measures**

• **Description of first aid measures**

• **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)



**Trade name: TRIGGERFOAM PRO WINDOW AND DOOR**

(Contd. of page 2)

- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**  
If skin irritation continues, consult a doctor.  
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
Foam  
CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
In case of fire, the following can be released:  
Nitrogen oxides (NO<sub>x</sub>)  
Carbon monoxide (CO)  
Hydrogen cyanide (HCN)
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
- **Additional information**  
Cool endangered receptacles with water spray.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Keep away from ignition sources  
Ensure adequate ventilation  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow to enter sewers/ surface or ground water.  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

US

(Contd. on page 4)



Trade name: TRIGGERFOAM PRO WINDOW AND DOOR

(Contd. of page 3)

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure that suitable extractors are available on processing machines  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:**  
Do not store together with acids.  
Do not store together with alkalis (caustic solutions).  
Store away from oxidizing agents.
- **Further information about storage conditions:**  
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.  
Protect from humidity and water.  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:**  
No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

|  |   |
|--|---|
| <b>CAS: 115-10-6 dimethyl ether</b>  |   |
| WEEL   | Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm                                  |
| <b>CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues</b> |   |
| WEEL   | Short-term value: 0.07 mg/m <sup>3</sup><br>Long-term value: 0.02 mg/m <sup>3</sup> |

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

(Contd. on page 5)

**Trade name: TRIGGERFOAM PRO WINDOW AND DOOR**

(Contd. of page 4)

- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

|               |                                    |
|---------------|------------------------------------|
| <b>Form:</b>  | Aerosol                            |
| <b>Color:</b> | According to product specification |
| <b>Odor:</b>  | Characteristic                     |

- **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** Undetermined.

- **Flash point:** Not applicable, as aerosol.

- **Ignition temperature:** 199 °C (390.2 °F)

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Heating may cause an explosion.

- **Explosion limits:**

|               |            |
|---------------|------------|
| <b>Lower:</b> | 3.0 Vol %  |
| <b>Upper:</b> | 18.6 Vol % |

- **Density:** Not determined.

(Contd. on page 6)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/24/2020

Reviewed on 03/24/2020

**Trade name: TRIGGERFOAM PRO WINDOW AND DOOR**

(Contd. of page 5)

- **Solubility in / Miscibility with Water:** Insoluble.
- **Solvent content:**
- **VOC content:** 18.3 %
- **Other information** No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**  
Hydrogen cyanide (prussic acid)  
Carbon monoxide  
Nitrogen oxides (NOx)

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**CAS: 115-10-6 dimethyl ether**

|            |          |                |
|------------|----------|----------------|
| Inhalative | LC50/4 h | 308 mg/l (rat) |
|------------|----------|----------------|

**CAS: 13674-84-5 tris(2-chlorisopropyl)-phosphate**

|      |      |                   |
|------|------|-------------------|
| Oral | LD50 | 3,600 mg/kg (rat) |
|------|------|-------------------|

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**  
Sensitization possible through inhalation.  
Sensitization possible through skin contact.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

|                |  |   |
|----------------|--|---|
| CAS: 9016-87-9 | diphenylmethanediisocyanate, isomeres and homologues | 3 |
|----------------|--|---|

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 7)



Trade name: TRIGGERFOAM PRO WINDOW AND DOOR

(Contd. of page 6)

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |                                       |                       |
|---------------------------------------|-----------------------|
| · <b>UN-Number</b>                    |                       |
| · <b>DOT</b>                          | UN1950                |
| · <b>IMDG, IATA</b>                   | 1950                  |
| · <b>UN proper shipping name</b>      |                       |
| · <b>IMDG</b>                         | AEROSOLS              |
| · <b>IATA</b>                         | AEROSOLS, flammable   |
| · <b>Transport hazard class(es)</b>   |                       |
| · <b>DOT, IMDG, IATA</b>              |                       |
| · <b>Class</b>                        | 2.1                   |
| · <b>Label</b>                        | 2.1                   |
| · <b>Packing group</b>                |                       |
| · <b>DOT, IMDG, IATA</b>              | Void                  |
| · <b>Environmental hazards:</b>       |                       |
| · <b>Marine pollutant:</b>            | No                    |
| · <b>Special precautions for user</b> | Warning: Gases        |
| · <b>EMS Number:</b>                  | F-D,S-U               |
| · <b>UN "Model Regulation":</b>       | UN1950, Aerosols, 2.1 |

US

(Contd. on page 8)

Trade name: TRIGGERFOAM PRO WINDOW AND DOOR

(Contd. of page 7)

### 15 Regulatory information

• **Safety, health and environmental regulations/legislation specific for the substance or mixture**

• **Sara**

• **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

• **Section 313 (Specific toxic chemical listings):**

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

• **TSCA (Toxic Substances Control Act):**

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

CAS: 13674-84-5 tris(2-chlorisopropyl)-phosphate

CAS: 115-10-6 dimethyl ether

• **Proposition 65**

• **Chemicals known to cause cancer:**

None of the ingredients is listed.

• **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

• **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

• **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

• **Carcinogenic categories**

• **EPA (Environmental Protection Agency)**

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

D;CBD

• **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

• **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

• **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

• **Hazard pictograms**



GHS02 GHS07 GHS08

• **Signal word** Danger

• **Hazard-determining components of labeling:**

diphenylmethanediisocyanate, isomeres and homologues

• **Hazard statements**

Extremely flammable aerosol.

Pressurized container: May burst if heated.

May cause long lasting harmful effects to aquatic life.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Harmful if inhaled.

(Contd. on page 9)





**Trade name: TRIGGERFOAM PRO WINDOW AND DOOR**

(Contd. of page 8)

- Suspected of causing cancer.
- May cause harm to breast-fed children.
- May cause respiratory irritation.
- May cause damage to organs through prolonged or repeated exposure.
- **Precautionary statements**
  - Obtain special instructions before use.
  - Keep out of reach of children.
  - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
  - Do not spray on an open flame or other ignition source.
  - Do not pierce or burn, even after use.
  - Do not breathe vapours/spray.
  - Wear protective gloves/protective clothing/eye protection.
  - In case of inadequate ventilation wear respiratory protection (a protective mask with an appropriate gas filter - i.e. type A1 according to standard EN 14387).
  - If on skin: Wash with plenty of water/soap.
  - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
  - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  - IF exposed or concerned: Get medical advice/attention.
  - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
  - Dispose of container to in accordance with local/regional/national/international regulation.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

- Flam. Aerosol 1: Aerosols – Category 1
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
- Resp. Sens. 1: Respiratory sensitisation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Carc. 2: Carcinogenicity – Category 2
- Lact.: Reproductive toxicity – effects on or via lactation
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2