

i Product iQ will be unavailable on Saturday, April 13th from 8:00am to 1:00pm CST due to site maintenance. We apologize for any inconvenience.



Caulking and Sealants Certified for Canada

[See General Information for Caulking and Sealants Certified for Canada](#)

DEWALT INDUSTRIAL TOOL CO

R16754

701 E Joppa Rd
Towson, MD 21286 USA

A sealant as applied to inorganic reinforced cement boards.

**Classification
or Rating +**

Flame Spread	10
Smoke Developed	30

**Classification
or Rating+**

Flame Spread	5
Smoke Developed	10

+ - Tested as applied in three 19mm diameter beads, 127mm oc covering 12.5 percent of the exposed test area.

**TriggerFoam Pro Window and Door
Applied to Inorganic
Reinforced Cement Board+**

Flame spread	0
Smoke developed	10

+Tested as applied in three 3/4 in. diameter beads, 5 in. OC covering 12.5 percent of the exposed test sample area.

**TriggerFoam Pro All Season
Applied to Inorganic
Reinforced Cement Board+**

Flame spread	0
Smoke developed	10

+Tested as applied in three 3/4 in. diameter beads, 5 in. OC covering 12.5 percent of the exposed test sample area.

**Trigger Foam Pro Fire Block
Applied to Inorganic
Reinforced Cement Board+**

Flame spread	0
Smoke developed	10

+Tested as applied in three 3/4 in. diameter beads, 5 in. OC covering 12.5 percent of the exposed test sample area.

**Trigger Foam Pro Window & Door
Applied to Inorganic
Reinforced Cement Board+**

Flame spread	0
Smoke developed	10

+Tested as applied in three 3/4 in. diameter beads, 5 in. OC covering 12.5 percent of the exposed test sample area.

**Trigger Foam Pro All Season
Applied to Inorganic
Reinforced Cement Board+**

Flame spread	0
Smoke developed	10

+Tested as applied in three 3/4 in. diameter beads, 5 in. OC covering 12.5 percent of the exposed test sample area.

A prepackaged, pressurized, one-component expanding foamed plastic sealant certified in accordance with CAN/ULC-S102 as indicated.

**DEWALT POWER FOAM
Applied to Inorganic Reinforced Cement Board++**

Flame spread	5
Smoke developed	35

**DEWALT POWER RESIDENT
Applied to Inorganic Reinforced Cement Board++**

Flame spread	5
Smoke developed	35

**DEWALT TRIGGER FOAM PRO FIRE BLOCK FORMULA
Applied to Inorganic Reinforced Cement Board++**

Flame spread	10
Smoke developed	20

**DEWALT TRIGGER FOAM PRO STANDARD FORMULA
Applied to Inorganic Reinforced Cement Board++**

Flame spread	10
--------------	----

Smoke developed	20
-----------------	----

++Tested as applied in three 19 mm diameter beads, spaced 100 mm OC covering 12.7 percent of the exposed test sample area.

Last Updated on 2020-06-01

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."